

Material

- Glazed titanium steel


Features

- ANTIGLISS included
- Integrated tile flanges
- Option made to measure



Compatible drain fittings

- Geberit offset, ABS 151.602.21.1 (polished chrome)
- Geberit offset, PP 150.183.00.1 (rough-in unit)
- Geberit offset, brass 151.450.00.1 (rough-in unit)
- Mountain Plumbing offset, brass BDR20SBR22/FFF (cable drive)
- Mountain Plumbing offset, ABS BWO40S22A2/FFF (cable drive)
- Mountain Plumbing offset, PVC BWO40S22P2/FFF (cable drive)
- OS&B direct, brass 307DQ-25FFF (clicker)
- OS&B offset, PVC 5100QK-FFF (clicker)



Variant no

Color

Tile flange

<input type="checkbox"/> 2241-0002	C1 white gloss	TF00 no tile flange
<input type="checkbox"/> 2241-0003	C1 white gloss	TF01 Tile flange on 3 sides, drain left
<input type="checkbox"/> 2241-0004	C1 white gloss	TF02 Tile flange on 3 sides, drain right
<input type="checkbox"/> 2241-0005	C1 white gloss	TF03 Tile flanges left / back, drain left
<input type="checkbox"/> 2241-0006	C1 white gloss	TF04 Tile flanges right / back, drain right

Colors

C058 White matte



C__ Color class C, D

[↗ color list](#)

Options

CE1 CLEANEFECT

HC2 Handle CONTURA

HS2 Handle SAFE

Special length / width -1"/+2"

Accessories

109547

Schmidlin ELEMENT, magnetic candle holder

101187

Schmidlin RELAX bathtub pillow, black, 1 piece

117005


Schmidlin 2-corner tape-flange, 155" (4m)

109810

Schmidlin adjustable installation feet (4 pieces)

101196

Schmidlin mounting angle for tile flange (SIA 181), 4 pieces



Technical Information

Installation location	corner
Weight without water	119 lbs
Water depth to overflow	13 1/2"
Max. water capacity to overflow	60 gal
Drain opening	2"
Overflow hole diameter	2"



[↗ Installation Instructions](#)

Standards / Codes

- This product complies with
- ASME A112.19.1 / CSA B45.2
- ASTM F462
- ADA



Meets the Americans with Disabilities Act guidelines and
ANSI A117.1 requirements for accessibility and usability -
check local code. Install with seat at head end.

Notes

- Right hand outlet shown
- Bath faucet not included
- Refer to installation instructions
- We recommend the use of Schmidlin adjustable installation feet

Important: Dimensions of fixtures are nominal and may vary within the range tolerances established by ANSI standard A112.19.4. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

02/06/2026 Subject to technical changes.